## Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of claims:**

Claims 1-29 (canceled)

- 30. (Previously Presented) A system for analysis of one or more biomolecules, comprising: (a) a microdevice comprised of (i) a substrate; (ii) a separation channel formed in said substrate, (iii) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (b) means for causing at least a portion of said one or more biomolecules to migrate along said separation channel, thereby separating said one or more biomolecules; and (c) information stored in said memory about a character or a sequence of said one or more biomolecules.
- 31. (Previously Presented) The system of claim 30, wherein said substrate comprises a plate, wafer, chip, slide, or disc.
- 32. (Previously Presented) The system of claim 30, wherein said means for causing at least a portion of said one or more biomolecules to migrate along said separation channel comprises an electric field.
- 33. (Previously Presented) The system of claim 32, further comprising one or more electrodes each capable of being connected to a power source, the one or more electrodes being disposed with respect to at least one of said separation channels for generating said electric field along at least a portion thereof.
- 34. (Previously Presented) The system of claim 30, wherein said means for causing at least a portion of said one or more biomolecules to migrate along said separation channel comprises a centrifugal force.

- 35. (Previously Presented) The system of claim 34, wherein said microdevice is a spinning-disc microdevice.
- 36. (Previously Presented) The system of claim 35, wherein said memory is an optical memory.
- 37. (Previously Presented) The system of claim 30, wherein the microdevice comprises a plurality of separation channels and said separation channels are non-intersecting.
- 38. (Previously Presented) The system of claim 30, wherein the rewritable memory is permanently affixed to the substrate.
- 39. (Previously Presented) The system of claim 30, wherein the rewritable memory comprises at least one of an integrated circuit memory, an optical memory, a thin film semiconductor memory, a ferromagnetic memory, a molecular memory, and a biomolecular memory.
- 40. (Previously Presented) The system of claim 30, wherein said memory includes a storage capacity of at least 1 megabyte.
- 41. (Previously Presented) The system of claim 30, further comprising a detector in optical communication with at least a region of the separation channel.
- 42. (Previously Presented) The system of claim 30, further comprising a temperature-control device adapted to modulate the temperature of at least a portion of said substrate.
- 43. (Currently Amended) A system for the analysis of one or more biomolecules, comprising: (a) a substrate; (b) an array of polynucleotides supported by said substrate; (c) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (d) a temperature-control device adapted to regulate the temperature

of at least a portion of said substrate; and (d) (e) information stored in said memory about a character or a sequence of said one or more biomolecules.

- 44. (Currently Amended) The system of claim 43, wherein the further comprising a temperature-control device is adapted to modulate the temperature of at least a portion of said substrate.
- 45. (Previously Presented) The system of claim 43, further comprising a detector in optical communication with at least a portion of said substrate.
- 46. (Previously Presented) A system for the analysis of one or more biomolecules, comprising: (a) a substrate; (b) one or more microscale structures in said substrate configured to support one or more biomolecule-containing samples; (c) a rewritable optical memory integrated into said substrate, with said memory being adapted for storing binary coded information.
- 47. (Previously Presented) The system of claim 46, further comprising a temperature control device adapted to modulate the temperature within at least one of the one or more microscale structures.
- 48. (Previously Presented) The system of claim 46, further comprising a detector in optical communication with at least one of said one or more microscale structures.
- 49. (Previously Presented) A system for analysis of one or more biomolecules, comprising: (a) a microdevice comprised of (i) a substrate; (ii) a separation channel formed in said substrate, (iii) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (b) means for causing at least a portion of said one or more biomolecules to migrate along said separation channel, thereby separating said one or more biomolecules; and (c) machine-readable code, executable by a computer, stored in said memory.

- 50. (Currently Amended) A method for analyzing one or more biomolecule-containing samples, comprising: (a) providing a microdevice comprised of (i) a substrate, (ii) one or more microscale structures in said substrate configured to support said one or more biomolecule-containing samples, and (iii) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (b) providing a station adapted to receive said microdevice, with said station configured to carry out (i) sample processing, and (ii) reading and writing of binary coded information; (c) introducing at least one biomolecule-containing sample into at least one of said one or more microscale structures; (d) placing said microdevice within said station; (e) regulating the temperature of at least a portion of said microdevice; (f) processing said sample within said station; and (f) (g) after said processing, with said microdevice in said processing station, storing information in said memory about results or output generated from use of said processing station.
- 51. (Currently Amended) The method of claim 50, wherein said processing regulating includes modulating the temperature within at least one of the one or more microscale structures.
- 52. (Previously Presented) A microdevice for analysis of one or more biomolecules, comprising: a substrate; one or more microscale structures in said substrate configured to support one or more biomolecule-containing samples; a memory integrated into said substrate; machine-readable code stored in said memory; and a microprocessor integrated into said substrate, capable of executing said code.
- 53. (Previously Presented) The microdevice of claim 52, wherein said microscale structures include one or more of: channels, wells, chambers, reservoirs, and any combination thereof.
- 54. (Previously Presented) A microdevice for analysis of one or more biomolecules, comprising: a substrate; a polynucleotide array supported by said substrate; a memory integrated

into said substrate; machine-readable code stored in said memory; and a microprocessor integrated into said substrate, capable of executing said code.

- 55. (Previously Presented) A system for analysis of one or more biomolecules, comprising: (a) a microdevice comprised of (i) a substrate; (ii) a separation channel formed in said substrate, (iii) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (b) means for causing at least a portion of said one or more biomolecules to migrate along said separation channel, thereby separating said one or more biomolecules; and (c) a sample tracking device capable of storing information in said memory about a character or a sequence of said one or more biomolecules.
- 56. (Currently Amended) A system for the analysis of one or more biomolecules, comprising: (a) a substrate; (b) an array of polynucleotides supported by said substrate; (c) a rewritable memory integrated into said substrate, with said memory being adapted for storing binary coded information; (d) a temperature-control device adapted to regulate the temperature of at least a portion of said substrate; and (d) (e) a sample tracking device capable of storing information in said memory about a character or a sequence of said one or more biomolecules.